



**AMENDMENTS TO THE CLAIMS**

The following is a complete, marked up listing of revised claims with a status identifier in parentheses, underlined text indicating insertions, and strikethrough and/or double-bracketed text indicating deletions.

**LISTING OF CLAIMS**

1. (Previously Presented) A method of tracking a user in a communication network supporting a broadcast-multicast service, comprising:  
  
    classifying groups of users into tracking areas at the network;  
  
    transmitting an overhead message including an indicator value to at least one user of a group; and  
  
    tracking movement of the at least one user of the group based on a tracking area registration update message received from the user that is enabled or disabled based on the indicator value.
2. (Original) The method of claim 1, wherein the classifying step further includes classifying non-overlapping sectors into broadcast-multicast service tracking areas, each sector including one or more multicast groups of users.
3. (Original) The method of claim 1, further comprising:  
  
    determining a change in tracking area for the at least one user based on one of an adding criteria and a dropping criteria.

4. (Original) The method of claim 3, wherein  
each tracking area includes one or more groups of sectors, each sector including one or more multicast groups of users, and  
the adding criteria and dropping criteria includes comparing pilot signal strengths of sectors to at least one threshold.
5. (Original) The method of claim 1, wherein the tracking step further includes:  
tracking the user based on information related to a tracking area change received from the user.
6. (Cancelled)
7. (Cancelled)
8. (Original) The method of claim 1, wherein the tracking step further includes:  
tracking the user based on a registration message received from the user subsequent to a detection of a tracking area change by the user.
9. (Original) The method of claim 1, wherein  
non-overlapping tracking areas are defined and consist of one or more sectors in the network, and  
the tracking step further includes:

the network transmitting information related to the tracking areas of current and neighboring sectors; and

the user responding to these transmission to enable tracking of the user by the network.

10. (Original) The method of claim 5, wherein the information related to tracking areas is included in system overhead transmitted to the one or more sectors.

11. (Previously Presented) A method by which a user provides a tracking area registration update to a network supporting a broadcast-multicast service, the network serving a plurality of tracking areas, each tracking area containing one or more non-overlapping sectors, comprising:

receiving an overhead message including an indicator value from a serving sector;  
enabling a tracking area registration update message based on the indicator value received in the overhead message; and

sending a tracking area registration update message to the network to update the location of the user.

12. (Original) The method of claim 11, wherein detecting a change in tracking area is based on a trigger.

13. (Original) The method of claim 12, wherein the trigger is based on expiration of a given time interval to control rate at which registration messages are sent on the uplink.

14. (Original) The method of claim 12, wherein the trigger is based on a comparison of pilot signal strengths of one or more sectors of a tracking area to a given threshold.
15. (Original) The method of claim 12, wherein the trigger is based on pilot signal strengths of one or more sectors of a tracking area exceeding a given threshold or falling below a given threshold for a given period of time.
16. (Cancelled)
17. (Currently Amended) A method of tracking a user in a communication network supporting a broadcast-multicast service, the network serving a plurality of tracking areas, each tracking area containing one or more non-overlapping sectors, each sector having one or more groups of users, comprising:
- transmitting an indicator value in an overhead message for enabling or disabling tracking area updates from users of the sector; and
  - determining user location of at least one user within one of the tracking areas based on a response from the at least one user to the indicator value.
18. (Original) The method of claim 17, wherein the determining step includes:
- after expiration of a given time interval, the user evaluating pilot strengths of M strongest sectors against a given criteria to determine a change in tracking area, and
  - the network receiving the response based on a result of the evaluation, the response embodied as a tracking area update registration message from the user.

19. (Withdrawn) In a network supporting a broadcast-multicast service and serving a plurality of sectors, groups of sectors further classified by the network into a plurality of tracking areas, each sector having one or more groups of users, a method by which a user determines a change in tracking area, comprising:

receiving mapping data that maps a given sector identifier for a neighboring sector to a given tracking area to create associations that are known to each user of a group; and  
determining a change in tracking area based on the mapping data.

20. (Withdrawn) The method of claim 19, further comprising:

determining the mapping data based on one or more of pilot PN offset detection, primary scrambling code detection and explicit signaling from the network.

21. (Withdrawn) In a network supporting a broadcast-multicast service and serving a plurality of sectors, groups of sectors further classified by the network into a plurality of tracking areas, each sector having one or more groups of users, a method by which a user indicates a tracking area change to the network, comprising:

the network transmitting a list of candidate neighbor sectors to each sector, the list including pilot signal strength data of the sectors;

the user

comparing the pilot signal strengths of the candidate neighbor sectors on the list to determine changes in tracking area from a previous transmission; and

transmitting a registration message indicting a change in tracking area to the network, based on the comparing.

22. (Withdrawn) The method of claim 21, further comprising  
the network assigning indictor bits to neighbor sectors of the list, and, after a given time interval,  
the user evaluating candidate neighboring sectors corresponding to the indicator bits.
23. (Withdrawn) In a network supporting a broadcast-multicast service and serving a plurality of sectors, groups of sectors further classified by the network into a plurality of tracking areas, each sector having one or more groups of users, a method by which a user determines a tracking area, comprising:  
classifying neighboring sectors belonging to the same tracking area into an ordered candidate neighbor sector list;  
each sector transmitting a bitmap of sector identifiers to indicate whether a tracking area of a current sector is different from the tracking area of a previous sector in the candidate neighbor sector list, so that a user knows each sector identifier;  
the user accessing the bitmap to determine if its tracking area matches the tracking area of a sector transmitting the bitmap.
24. (Withdrawn) The method of claim 23, further comprising  
the network assigning indicator bits to represent neighbor sectors of the ordered candidate neighbor list; and

the accessing the bitmap step further comprising the user looking up an indicator bit for a particular sector to determine if the sector's tracking area matches that of the user.

25. (Previously Presented) In a network supporting a broadcast-multicast service and serving a plurality of sectors, groups of sectors further classified by the network into a plurality of tracking areas, each sector having one or more groups of users, a method of obtaining registration to track location of a user in a tracking area, comprising:

transmitting an overhead message from each sector to its corresponding groups of users, the overhead message including an indicator value enabling or disabling a registration update message from the users; and

receiving a registration from at least one user that is based on user detection of the indicator value.

26. (New) The method of claim 17, wherein the transmitting step transmits an indicator value enabling registration update messages if the users are in a sector on a boundary between at least two tracking areas and transmits an indicator value disabling the tracking area registration update message if the users are not in a sector on the boundary or an uplink is overloaded.